
Panel PC

- Powered by an 11th generation Intel Celeron processor, equipped with Windows 11 operating system
- Full 10.1-inch HD display, the IP65-rated front panel protects against water and dust ingress
- Excellent environmental adaptability, anti-electromagnetic interference and anti-static capabilities
- Fanless design, using large-area uniform heating fin, running 24/7 without affecting reliability and service life
- Rich interfaces, including multiple USB/LAN/HDMI and other I/O ports, easily meet various scenario requirements
- Dual-band Wi-Fi, Bluetooth 5.0, and expandable 4G (M.2 interface), multiple network connection modes
- Wide voltage and temperature design, can operate normally even under external voltage fluctuations or in extremely hot or cold conditions
- Standard PPC mounting hook component, easy to install and supports various installation methods such as embedded and wall-mounted



N5100 Processor






Windows 11 **Operating System**



Dual-band WiFi Running 24/7 without affecting reliability



10.1 inch screen



Rich interface extensions



700 cd/m² Brightness



storage expansion



800*1280

Screen resolution



IP65



INERUgged

Panel PC P10J Specifications





Windows 11 Home Optional: Windows 11 pro



Dimension/Weight

257.2*170*45.95mm 1.2kg



Buttons

Power (with indicator) *1



Strain Adapter

Input: 100~240V AC 50/60Hz Output: 12VDC4.0A



I/O Interface

Standard USB-A USB3.0*2 +USB2.0*2 Power interface DC IN 12V-24V Power connector *1" ∮ 3.5mm Standard Earphone Jack *1 RJ45 *2 DB9 PORT RS232 *2 HDMI 2.0a *1



♥ Tel: 400-830-4882 www.onerugged.com





Memory

RAM: 8GB ROM: 128GB (M.2 interface, SATA III signal)



Display

Type: LCD Size: 10.1 inch 16:10 Resolution: 800×1280 Brightness:700 cd/m²



The Internet

Optional 4G/Dual frequency WIFI/BT5.0



Certification

Front panel IP65



* The technical specifications of this product are subject to change without prior notice

⊠ inquiry@onerugged.com

🖉 Room 401, Building C, Chaojie Industrial Park, No. 1 Guanghui Road, Jinsha Community, Kengzi Street, Pingshan District, Shenzhen, China

INERUgged





Rugged Features

Working temperature: -20 °C to 60 °C Storage temperature: -30 °C to 70 °C Humidity: 95% Non-Condensing