EM-Q885M Rugged Tablet PC **Built to Conquer** Any Task C 0 l**ΠΠ**) 0 Android C 81 •: ŵ ((•)) NI NEC

Performance

- ·Qualcomm Kryo™ 670 CPU and the Al–accelerated Qualcomm Hexagon™ 770 processor
- ·Android 14 OS, paired with 8GB+128GB of expansive memory
- ·8-inch screen, with a high-capacity 10000mAh battery

Communication

- \cdot Integrated with a 5G modem and RF system,it supports mmWave and sub–6 GHz bands
- \cdot TDD and FDD modes, and SA and NSA network deployments, covering nearly all critical regions worldwide
- \cdot Enhanced wireless connectivity with Wi–Fi 6E, BT5.2

Function

- ·GPS/GLONASS/Beidou navigation, L1+L5 dual-band positioning
- $\cdot \textsc{Supports}$ NFC fast card reading, multiple communication protocols
- $\cdot \textsc{Optional}$ QR Code Module, quickly scan various 1D and 2D barcodes

Reliability

- $\cdot \mbox{Constructed}$ with wear–resistant materials, shock–absorbing architecture, and protective corner design
- ·Certified with IP65 dust and water resistance
- •Rigorously tested to MIL–STD–810H standards,1.22m drop protection

Product Six Views



Pogopin



Specification Parameter

| Basic parameters | | | Performance param | | |
|------------------|---|---|------------------------|---------------|--|
| Dimension | 236.7 x 155.7 x 20.8mm | | CPU | Octa | |
| Weight | 820g | | OS | Andr | |
| Device Color | Black | | RAM | 8GB | |
| LCD | 8 inch FHD 16:10, 1200x1920, 550nits Optional: HD, Resolution: 800*1280, Brightness: 1000nits | | ROM | 1280 | |
| Touch Panel | 5-point Capacitive Touchscreen, Tempered Glass, G+G, Hardness: 7H | | Battery | | |
| Camera | Front 5.0MP Rear 13.0MP Supports autofocus, with flashlight | 1 | Capacity | 3.8V, | |
| I/O | USB 3.0 Type–A x 1, Type–C(Data&Charging) x 1 Nano–SIM x 2/Micro SD Supports up to 512GB x 1 +Nano–SIM x 1 (three–in–one card slot) HDMI x 1,12PIN Pogo Pin x 1, Φ3.5mm standard earphone jack x 1, | | Туре | Rem | |
| | | | Endurance | Abov Defa | |
| | DC Supports 5V/4A Charging x 1 Power Input 100–240VAC0.5A50/60Hz | | RTC | Built | |
| Power | DC Output 5V/4A | | Data Collection | | |
| Communicat | ion | | | Built | |
| WIFI | Wi–Fi 6E& DBS, IEEE 802.11a/ b/ g/ n/ ac/ ax, Wi–Fi 2 \times 2 MU–MIMO | | NFC | Supp Card | |
| Bluetooth | BT5.2(BLE) | | 2D | Optio Scan | |
| 2G/3G/4G/5G | 5G:SA/ NSA: n1/ 3/ 5/ 7/ 8/ 20/ 28/ 38/ 40/ 41/ 77/ 78/79 4G: B1/ 2/ 3/ 4/ 5/ 7/ 8/ 12/ 17/ 18/ 19/ 20/ 26/ 28/ 32/ 34/ 38/ 39/ 40/ 41/ 42 3G: B1/ 2/ 4/ 5/ 6/ 8/ 19 2G: B2/ 3/ 5/ 8 | | Reliability | | |
| | | | Operate Temperature | -20 | |
| | | | Store Temperature | -30 | |
| | | | Humidity | 95% | |
| GNSS | Supports: GPS/GLONASS/BDS; Dual-frequency L1 + L5; | | Rugged Feature | IP65 | |
| | | | Drop Height | 1.22 | |

| Performance parameter | | |
|------------------------|--|--|
| CPU | Octa-core 2.7G ARM | |
| OS | Android 14/GMS | |
| RAM | 8GB LPDDR4x | |
| ROM | 128GB EMMC | |
| Battery | | |
| Capacity | 3.8V/10000mAh | |
| Туре | Removable Polymer Lithium-ion Battery | |
| Endurance | Above 8 hrs (Default 50% volume, Connected to WiF Default 200 nits brightness, Playing 1080P HD video | |
| RTC | Built-in rechargeable 3V/1mAh lithium-ion battery | |
| Data Collec | tion | |
| NFC | Built-in, 13.56MHz, Supports 14443A/14443B/15693 of ISO/IEC Card reading distance: 0–4cm | |
| 2D | Optional, Optical resolution: 5mil Scanning speed: 50 times/s | |
| Reliability | | |
| Operate Temperature | –20 °C ~ 60 °C | |
| Store Temperature | –30 °C ∼ 70 °C | |
| Humidity | 95% Non-Condensing | |
| Rugged Feature | IP65 certified, MIL-STD-810H certified | |
| Drop Height | 1.22m | |

Application Range

Emdoor

Various modules and accessories can be selected to meet customers' application in various industries.



in

Y

Tel: +86-(0)755-2372 2880 Web: www.emdoorrugged.com Email: marketing.info@emdoor.com